



# Wireless fire alarm system Specifications

Addressable



## Key attributes

Place of Origin	Taipei , Tiawan
Brand Name	GUARD max
Model Number	GU-98000
Product name	Wireless Addressable Fire Alarm Control Panel
Dimensions	274.5x201x74.8 mm
Supply Voltage	220~240 VAC@50/60 Hz
Operating voltage	3V DC
Battery	3.7V 3AH rechargeable battery
RF Frequency	433.92 MHz
RF Receiving Distance	≤ 100m( in an open area)
Points of input number	250pcs
Siren output	2 pcs
Degree of protection	IP20

## Packaging and delivery

Packaging Details	White box or as customer customized
Port	Taipei , Tiawan
Selling Units:	Single item
Single package size:	30X22X10 cm
Single gross weight:	3.000 kg

## FEATURES

- \* It allows to separate the installation in detection and alarm zones.
- \* Timer.
- \* Device shielding function



- \* Operation and configuration are regulated by the access levels with passwords.
- \* Main power explosion-proof and over voltage protection.
- \* Main power short circuit protection.
- \* One 3.7V rechargeable backup battery.

Product Name	Wireless Addressable Fire Alarm Control Panel	Consumption of AC network of supervision	8 W
Model	GU-98000	Operating voltage	3V DC
Material of panel	metal	Supply Voltage	220~240 VAC@50/60 Hz
Siren output	2pcs	Points of input number	250pcs devices
RF Frequency	433.92 MHz	RF Receiving Distance	≤ 120m( in an open area)
AC Supply fuse	0.5A	Battery	3.7V 3AH rechargeable battery
Net Weight	2.2kg	Dimension	274.5x201x74.8 mm

